

PARTS & SERVICE: 0208 988 7400

E-mail: Parts@clarkeinternational.com or Service@clarkeinternational.com

SALES: UK 01992 565333 or Export 00 44 (0)1992 565335

CIAPLE INTERNATIONAL Hemnall Street, Epping, Essex CM16 4LG www.clarkeinternational.com



# Platform Deck For FPL2/3

MODEL NO: P2 PART No: 3500216

ASSEMBLY INSTRUCTIONS

GC0219 REV 3

Thank you for purchasing this CLARKE Platform Deck.

Before attempting to use the P2 deck, please read this and the FPL2/3 manual and follow the instructions carefully. In doing so you will ensure the safety of yourself and that of others around you, and you can look forward to the ladder and deck giving you long and satisfactory service.

#### **CLARKE GUARANTEE**

This CLARKE product is guaranteed against faulty manufacture for a period of 12 months from the date of purchase. Please keep your receipt as proof of purchase.

This guarantee is invalid if the product is found to have been abused or tampered with in any way, or not used for the purpose for which it was intended.

Faulty goods should be returned to their place of purchase, no product can be returned to us without prior permission.

This guarantee does not effect your statutory rights.

### **Specifications**

The platform deck consists of two parts, one long and one short platform. These can be used singly or together depending on the ladder configuration being used.

#### Safety

For your safety and that of others around you, read the FPL2/3 instruction manual thoroughly before attempting to use the platform deck.

#### Assembly

Refer to the ladder configurations (G, H, and I) in the FPL2/3 instruction manual.


Decide the configuration required and install in the position it is to be used, ensuring it is firm and stable.


Please note that the details and specifications contained herein, are correct at the time of going to print. However, CLARKE International reserve the right to change specifications at any time without prior notice.

## CEDANTE ROB

#### Fit the decks as follows.


Place deck onto the ladder with the lip and lugs facing downwards as in Fig. 1. Ensure the lip on the tail end of the deck is pushed firmly up to the first ladder rung.





Lower the deck until it lies flat, (Fig. 2) with the lip pushed up to the first ladder rung. The other end of the deck should be covering half of the rung it is lying on.

Check the deck is fitted safely by trying to push it from side to side as in Fig. 3. The deck should not move if fitted correctly as it will be held in place by the lip and the two lugs.






Fig. 4 shows correct alignment of lip and lugs to prevent sideways movement.

Canales