


SAFETY DATA SHEET Swarfega Duck Oil Aerosol

SECTION 1: Identification of th	ne substance/mixture and of the company/undertaking	
1.1. Product identifier		
Product name	Swarfega Duck Oil Aerosol	
Product number	SDO500ML	
1.2. Relevant identified uses of	f the substance or mixture and uses advised against	
Identified uses	Lubricant. Car maintenance product.	
1.3. Details of the supplier of the	ne safety data sheet	
Supplier	Deb Ltd	
	Denby Hall Way	
	Denby	
	Derbyshire	
	DE5 8JZ	
	Main Tel. 01773 855100	
	Technical Tel 01773 855105	
	reach@deb.co.uk	
1.4. Emergency telephone nun	nber	
Emergency telephone	National Poisons Information Service (UK) 0844 8920111	
SECTION 2: Hazards identifica	ation	
2.1. Classification of the substa	ance or mixture	
Classification		
Physical hazards	Aerosol 1 - H222, H229	
Health hazards	Not Classified	
Environmental hazards	Not Classified	
Classification (67/548/EEC or 1999/45/EC)	F+;R12. R66.	
2.2. Label elements		
Pictogram		



Danger

H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated

Swarfega Duck Oil Aerosol

Precautionary statements	 P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/spray. P271 Use only outdoors or in a well-ventilated area.
Detergent labelling	\geq 30% aliphatic hydrocarbons,< 5% non-ionic surfactants
Supplementary precautionary statements	P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/informat 3.2. Mixtures	tion on ingredients		
BUTANE		10-	30%
CAS number: 106-97-8	EC number: 203-448-7		
Classification	Classificatio	on (67/548/EEC or 1999/45/EC)	
Flam. Gas 1 - H220	F+;R12		
Press. Gas			
ISO-BUTANOL			<1%
CAS number: 78-83-1	EC number: 201-148-0	REACH registration number: 01-	
		2119484609-23-0000	
Classification	Classificatio	on (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xi;R37/38,R41 R67		
Skin Irrit. 2 - H315			
Eye Dam. 1 - H318			
STOT SE 3 - H335, H336			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures 4.1. Description of first aid measures	
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.	
Ingestion	Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation.	
Skin contact	Prolonged skin contact may cause redness and irritation.	
Eye contact	Irritation of eyes and mucous membranes.	
4.3. Indication of any immedia	te medical attention and special treatment needed	
Notes for the doctor	No specific recommendations.	
SECTION 5: Firefighting meas	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with the following media: Powder. Dry chemicals. Water spray, fog or mist.	
5.2. Special hazards arising fr	om the substance or mixture	
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.	
Hazardous combustion products	Oxides of carbon.	
5.3. Advice for firefighters		
Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.	
SECTION 6: Accidental release measures		
6.1. Personal precautions, pro	tective equipment and emergency procedures	
Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.	
6.2. Environmental precautions		
Environmental precautions	Avoid discharge to the aquatic environment. Collect and dispose of spillage as indicated in Section 13.	
6.3. Methods and material for	containment and cleaning up	
Methods for cleaning up	Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.	
6.4. Reference to other section	ns	
Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards.	
SECTION 7: Handling and storage		
7.1. Precautions for safe hand	ling	
Usage precautions	Keep away from heat, sparks and open flame. Avoid spilling. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Avoid inhalation of vapours.	
7.2. Conditions for safe storag	e, including any incompatibilities	
Storage precautions	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.	
7.3. Specific end use(s)		

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.	
SECTION 8: Exposure Contr	rols/personal protection	
8.1. Control parameters Occupational exposure limits		
	nour TWA): WEL 600 ppm_1450 mg/m³ 5-minute):_WEL 750 ppm_1810 mg/m³	
ISO-BUTANOL		
	nour TWA): WEL 50 ppm 154 mg/m³ 5-minute): WEL 75 ppm 231 mg/m³	
WEL = Workplace Exposure	Limit	
Ingredient comments	WEL = Workplace Exposure Limits	
	Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64741-88-4)	
DNEL	Workers - Inhalation; Long term local effects: 5.4 mg/m ³ Consumer - Inhalation; Long term local effects: 1.2 mg/m ³	
8.2. Exposure controls		
Protective equipment		
Appropriate engineering controls	Provide adequate general and local exhaust ventilation.	
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.	
Hand protection	Use protective gloves. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.	
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.	
Hygiene measures	Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.	
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.	
SECTION 9: Physical and Cl	nemical Properties	
9.1. Information on basic phy	vsical and chemical properties	
Appearance	Aerosol.	
Colour	Brown.	

Odour	Characteristic.
-------	-----------------

Flash point	-15°C
-------------	-------

Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8% Upper flammable/explosive limit: 9.0%
Solubility(ies)	Insoluble in water
9.2. Other information	
Other information	None.
SECTION 10: Stability and re	activity
10.1. Reactivity	
Reactivity	Vapours may form explosive mixtures with air.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	Not determined.
10.4. Conditions to avoid	
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.
10.5. Incompatible materials	
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
10.6. Hazardous decompositi	on products
Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).
SECTION 11: Toxicological in	nformation
11.1. Information on toxicolog	jical effects
Inhalation	May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.
Skin contact	Product has a defatting effect on skin. May cause skin irritation/eczema. Prolonged or repeated exposure may cause severe irritation.
Eye contact	Irritating to eyes. May cause chemical eye burns.
Route of entry	Inhalation Skin and/or eye contact.
SECTION 12: Ecological Info	rmation
Ecotoxicity	Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability	The product is expected to be slowly biodegradable. The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request, or at the request of a detergent manufacturer.
12.3. Bioaccumulative potentia	<u>l</u>
Bioaccumulative potential	No data available on bioaccumulation.
12.4. Mobility in soil	
Mobility	The product has poor water-solubility.
12.5. Results of PBT and vPvB	B assessment
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
12.6. Other adverse effects	
Other adverse effects	None known.
SECTION 13: Disposal conside	erations
13.1. Waste treatment method	S
General information	Do not puncture or incinerate even when empty. Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Disposal methods	Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
SECTION 14: Transport inform	nation
General	No other information known.
14.1. UN number	
UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	
	1950
14.2. UN proper shipping name	
14.2. UN proper shipping name	9
14.2. UN proper shipping name Proper shipping name (ADR/RID) Proper shipping name	AEROSOLS AEROSOLS
14.2. UN proper shipping name Proper shipping name (ADR/RID) Proper shipping name (IMDG)	AEROSOLS AEROSOLS AEROSOLS
14.2. UN proper shipping name Proper shipping name (ADR/RID) Proper shipping name (IMDG) Proper shipping name (ICAO)	AEROSOLS AEROSOLS AEROSOLS AEROSOLS
14.2. UN proper shipping name Proper shipping name (ADR/RID) Proper shipping name (IMDG) Proper shipping name (ICAO) Proper shipping name (ADN)	AEROSOLS AEROSOLS AEROSOLS AEROSOLS
14.2. UN proper shipping nameProper shipping name(ADR/RID)Proper shipping name(IMDG)Proper shipping nameProper shipping name(ICAO)Proper shipping nameADN)14.3. Transport hazard class(e	AEROSOLS AEROSOLS AEROSOLS AEROSOLS AEROSOLS s)
14.2. UN proper shipping nameProper shipping name(ADR/RID)Proper shipping name(IMDG)Proper shipping nameProper shipping name(ICAO)Proper shipping nameADR/RID class	AEROSOLS AEROSOLS AEROSOLS AEROSOLS S) 2.1

ICAO class/division	2.1
Transport labels	
14.4. Packing group	
ADR/RID packing group	#
IMDG packing group	#
ICAO packing group	#
14.5. Environmental hazards	
Environmentally hazardous sul	bstance/marine pollutant
14.6. Special precautions for u	ser
EmS	F-D, S-U
Tunnel restriction code	(D)
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended)
	work (as amended). Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work.
	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information	
Revision comments	SDS amended in line with REGULATION (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures (as amended)
Revision date	15/05/2015

Revision	4
Supersedes date	30/09/2011
Risk phrases in full	 R10 Flammable. R12 Extremely flammable. R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	 H220 Extremely flammable gas. H222 Extremely flammable aerosol. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
Notes for Risk Phrases and Hazard Statements in Full	The full text for Risk Phrases and Hazard Statements in section 16 relates to the reference numbers in sections 2 and 3 and not necessarily the finished product classification.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.