

ERP Technical Information

Clarke Model: COB10T
Model Type: L9601J
General Description 10W COB LED Light Tripod

Reference to harmonised Standards

EN 60598-1:2015
EN 60598-2-4:1997
EN 60598-2-5:1998
EN 62493:2015
IEC 62778:2014
EN 55015:2013
EN 61547:2009
EN 61000-3-2:2014
EN 61000-3-3:2013

Specific Precautions

Portable LED Floodlight to be used indoors or outdoors
To be operated as prescribed by the Clarke Operating Manual

Measured Technical Parameters

Operating Voltage (V/Hz)	230 / 50
Operating Temperatures: (Min / Max °C)	- 20 to 50
LED Wattage Consumption	10W
Luminous Flux: (Lm)	800
Efficiency (Lm / W)	80
LED light Expectancy (hr):	20,000
LED Type:	A++, A+, A
LED manufacturer:	Epistar LED chip
Energy Efficiency Class:	A+
Stand:	Tripod
Tilt adjustment:	-90° to 90°
IP Rating:	IP 65
Insulation Class:	I
Colour Temperature:	6500k
Product weight(Kg):	3.5
LED Replaceable:	No
Supply cable assembly plug type:	Moulded 13A BS1362 Bussmann
Type of light	Floodlight