Model Identi	fier(s):	HL-E44A		(Devil 37	1SPC)		
Item	Symbol	Value	Unit		Item	Unit	
Heat Output				Type one).	of heat input for electric storage space l	heaters only (select	
Nominal heat output	P _{nom}	2.8	kW		al heat charge control, with integrated nostat	no	
Minimum heat output (indicative)	P_{min}	1.4	kW		al heat charge control, with room and / tdoor temperature feedback	no	
Maximum Continuous heat output	P _{max,c}	2.8	kW		onic heat charge control with room and tdoor temperature feedback	/ no	
Auxiliary electricity consumption				fan as	ssisted heat output	no	
At nominal N/A eat output el _{max} N/A kW			kW	Туре	Type of heat ouput/ room temperature control (select one)		
At minimum heat output	el _{min}	N/A	kW	_	stage heat output and no room erature control	no	
In standby Mode	el _{sв}	0	kW		r more manual stages, no room erature control	yes	
				with r	mechanic thermostat room temperature	no	
				with e	electronic room temperature control	no	
				with e	electronic room temperature control plu mer	s no	
					electronic room temperature control plu timer	s no	
				Other control options (mutiple selections possible)			
				room detec	temperature control, with presence tion	no	
				room detec	temperature control, with open windov	v no	
				with o	distant control option	yes	
				with a	adaptive start control	no	
				with v	working time limitation	no	
		_		with b	plack bulb sensor	no	
Contact Deta	ils	Clarke Inte	ernatio		plack bulb sensor emnall Street, Epping, CM1 4LG	no	