

HBS600DELUX_400V * // wood bandsaw



highlights

- precision tool for professionals
- fully enclosed and thickened steel body design, ensuring superior rigidity
- powerful 4 kW motor meets the demand for slicing thick hardwood
- industrial grade bandsaw blade guide, to ensure precision and convenience
- fine ground and thickened cast iron table with T-slot design, to ensure excellent surface flatness
- rack and pinion design to ensure that the cutting height adjustment is accurate, reliable and durable
- extra large rip-fence with solid guide rod ensures precision, smooth sliding and splendid handling
- thermal overload protection



HBS600DELUX_400V * // wood bandsaw



technical details

| | |
|--|---------------|
| motor power s6 in W | 6000 |
| voltage | 400V / 3x50Hz |
| swivel range | 0-20° |
| suction port in mm | Ø100 |
| max. cutting width at parallel fence in mm | 580 |
| saw band speed in m/min | 1500 |
| sound pressure level in dB(A) | 90 |
| gross weight in kg | 350 |
| packaging width in mm | 774 |
| EAN code | 9120058372391 |

| | |
|-------------------------------|---------------|
| motor power s1 in W | 4000 |
| total dimensions in mm | 1201x889x2017 |
| table size in mm | 700x608 |
| max. cutting height 90° in mm | 370 |
| saw band in mm | 4470x10 - 35 |
| flywheel diameter in mm | 600 |
| net weight in kg | 330 |
| packaging height in mm | 2.155 |
| packaging length in mm | 1.116 |