

FLOATING TREE

24 HOUR RUNNING



Floating Tree creates a stunning water display in any large pond or lake. Powered by a powerful submersible pump, coupled to the underside of three ballast tanks, the clearer water near the surface is pumped through an integral nozzle, creating a decorative fountain of up to 150cm high and 450cm wide. A minimum clear water depth of 60cm above damaging mud, silt, sediment and debris should be maintained during use, as it floats on the surface. It is simple to assemble, install and has three anchoring points.


Fluid: Water in ponds & lakes | Temperature: 0 - 40°C

Application: Ponds | Water features | Oxygenation | Decorative displays | Elegant centre-pieces

Floating Tree	Ballast tanks	Nozzle	Pump bracket
	Polypropylene & glass fibre	Polypropylene & glass fibre	Polypropylene & glass fibre

Pump	Impeller	Shaft seal	Outlet
	Open	Single Mechanical	Polypropylene
	Outer cover & handle	Pump casing	Impeller
	Polypropylene & glass fibre	Polypropylene & glass fibre	Nylon & glass fibre
	Shaft	Shaft seal	Strainer
	S/S 410	Silicon carbide & Viton	Polypropylene & glass fibre

Motor	Poles, protection	Enclosure	Insulation
	2 pole, IP68	Oil	Class B
	Thermal protection	Starting	Motor cover
	Integral	Internal capacitor	Aluminium



Integral nozzle



Floating Tree

item code	model	kW	volt	dia x h (mm)	fountain height (cm)	fountain width (cm)	dry weight (kgs)
15-10-1034	Floating Tree	0.45	230	Ø750 x 510	50-150	100-450	11.4