

TS315VF2000_230V // panel saw



highlights

- height- and angle adjustable saw blade with scoring unit
- grey cast iron table with extension on the right hand side and at the back of the table
- smoothly running 2000mm aluminium sliding table with rugged outrigger table incl. support roller
- extractable mitre at rip fence with work piece end stop
- XL cutting width at rip fence with max. 1260mm

included in delivery: T.C.T. circular saw blade Ø315mm, scoring unit, T.C.T. scoring unit saw blade, extensions, table extensions, rip fence, mitre fence, telescopic fence



TS315VF2000_230V // panel saw



technical details

motor power s1 in W	3000	motor power s6 in W	4000
voltage	230V	outrigger table in mm	540x760
sliding table in mm	2000x270	suction port in mm	100
table height in mm	870	table extension in mm	500x310 / 800x440
table size in mm	800x820	max. cutting width at parallel fence in mm	1220
max. cutting height 45° in mm	80	max. trimming in mm	1900
max. cutting height 90° in mm	100	scoring sawblade in mm	90
sawblade in mm	315	sawblade speed in min-1	4000
scoring unit speed in min-1	5800	sawblade swivel	0°-45°
gross weight in kg	284	net weight in kg	263
packaging length in mm	910	packaging width in mm	741
packaging height in mm	1.047	EAN code	9120039903934